

# ENVIRONMENTAL PRODUCT DECLARATION (EPD)

ACCORDING TO ISO 14025 & 15804+A2

PRODUCT: OMEGA I 2950/10

**casala**

# Environmental Product Declaration (EPD)

An Environmental Product Declaration (EPD) is a Type III environmental declaration that quantifies environmental information about the life cycle of a product. This can enable comparisons between products fulfilling the same function. The methodology to produce an EPD is based on the full product life cycle assessment (LCA), following the ISO 14040 series of standards.

## OMEGA I 2950/10

Omega is a stylish and comfortable seating range, recognisable by its slender felt shell made of recycled PET, combined with a lightweight steel frame. The diversity of its product family makes Omega a multifunctional all-rounder for the office, hospitality spaces and break out areas. Omega's shell is available in six colours. The wide range of finishes makes Omega a true chameleon. From classic to chic and always matching the interior. For extra sitting comfort, the Omega shell can be specified with an upholstered seat.



Casala's production facility has a solar park which produced 4.5t Kwh in 2023. The remaining energy needed is produced by European Wind as stated by the supplier. The production facility and almost all 3<sup>rd</sup> parties are ISO 9001 & 14001 certified.

Variant	Felt shell of recycled PET
Base	Welded steel chassis
Finish	Powder coating
Technical life span	15 years
Dimensions (HxLxW)	79 x 55 x 60 cm
Weight	6.9 kg
Packaging weight	0.1 kg

## GLOBAL WARMING POTENTIAL

To quantify and compare results, we use the Global Warming Potential (GWP) expressed in kg CO<sub>2</sub>-equivalent. This is a measurement method for finding out the amount of energy required to emit 1 tonne of a gas, which is absorbed over a 100-year period. The greater the GWP, the more a particular gas warms the earth.

To comply with EN ISO 15804+A2, Casala uses the 'cradle to grave' assessment for their EPD files. The assessment covers the full life cycle of a product; from production phase to use, followed by recycling or disposal. Other EPD files often only use the 'cradle to gate' assessment, which only covers the production phase.

GWP per unit (Cradle to Grave)	18.619 kg CO <sub>2</sub> eq.
GWP per unit (Cradle to Gate)	16.415 kg CO <sub>2</sub> eq.
Average GWP for contract chairs according to the Furniture Industry Research Association (Cradle to Gate)	27.000 kg CO <sub>2</sub> eq.

## THE ASSUMED PERCENTAGE OF WASTE PROCESSING

Landfill	5.71 %
Incineration	16.64 %
Recycling	77.16 %
Re-use	0.49 %

## DOCUMENT INFORMATION

Calculation number	ReTHiNK-82968
Declaration owner	Casala
Publisher	Casala
Program operator	Casaro
LCA software	NIBE - R<THiNK LCA
Status	Valid

