

ENVIRONMENTAL PRODUCT DECLARATION (EPD)

ACCORDING TO ISO 14025 & 15804+A2

PRODUCT: SHIFT 186/11

casala

Environmental Product Declaration (EPD)

An Environmental Product Declaration (EPD) is a Type III environmental declaration that quantifies environmental information about the life cycle of a product. This can enable comparisons between products fulfilling the same function. The methodology to produce an EPD is based on the full product life cycle assessment (LCA), following the ISO 14040 series of standards.

SHIFT 186/11

The minimalist design of Shift brings flexibility and style to any lobby. This collection of coffee tables and side tables is made of recycled steel. The models vary in height and can be easily combined and moved. The plastic trays, made entirely from 100% recycled material, serve as useful storage space and offer a stylish stage for decorative elements.

Casala's production facility has a solar park which produced 4.5t Kwh in 2023. The remaining energy needed is produced by European Wind as stated by the supplier. The production facility and almost all 3rd parties are ISO 9001 & 14001 certified.



Variant	coffee table high, 100 x 55 x 38 cm
Base	Welded steel chassis
Finish	Powder coating
Technical life span	15 years
Dimensions (HxLxW)	38 x 55 x 100 cm
Weight	24.6 kg
Packaging weight	0.1 kg

GLOBAL WARMING POTENTIAL

To quantify and compare results, we use the Global Warming Potential (GWP) expressed in kg CO₂-equivalent. This is a measurement method for finding out the amount of energy required to emit 1 tonne of a gas, which is absorbed over a 100-year period. The greater the GWP, the more a particular gas warms the earth.

To comply with EN ISO 15804+A2, Casala uses the 'cradle to grave' assessment for their EPD files. The assessment covers the full life cycle of a product; from production phase to use, followed by recycling or disposal. Other EPD files often only use the 'cradle to gate' assessment, which only covers the production phase.

GWP per unit (Cradle to Grave)	48.403 kg CO ₂ eq.
GWP per unit (Cradle to Gate)	79.543 kg CO ₂ eq.
Average GWP for steel pedestals according to the Furniture Industry Research Association (Cradle to Gate)	44.000 kg CO ₂ eq.

THE ASSUMED PERCENTAGE OF WASTE PROCESSING

Landfill	1.00 %
Incineration	0.41 %
Recycling	86.65 %
Re-use	11.95 %

DOCUMENT INFORMATION

Calculation number	ReTHiNK-88327
Declaration owner	Casala
Publisher	Casala
Program operator	Casaro
LCA software	NIBE - R<THINK LCA
Status	Valid

