

ENVIRONMENTAL PRODUCT DECLARATION (EPD)

ACCORDING TO ISO 14025 & 15804+A2
PRODUCT: CURVY TRAVERSE 1287/02 + 1288/99

casala

Environmental Product Declaration (EPD)

An Environmental Product Declaration (EPD) is a Type III environmental declaration that quantifies environmental information about the life cycle of a product. This can enable comparisons between products fulfilling the same function. The methodology to produce an EPD is based on the full product life cycle assessment (LCA), following the ISO 14040 series of standards.

CURVY TRAVERSE 1287/02 + 1288/99

Waiting brings out the importance of comfort and Curvy beam seating is optimally suited to offer both comfort and convenience as a two, three, or four seater. Curvy beam seating can be added to with table tops and linked to other seats to enable all sorts of variations. With Curvy you'll never mind waiting!

Casala's production facility has a solar park which produced 4.5t Kwh in 2023. The remaining energy needed is produced by European Wind as stated by the supplier. The production facility and almost all 3rd parties are ISO 9001 & 14001 certified.



Variant	plastic back, plastic seat, 2 seat
Base	Welded steel chassis
Finish	Powder coating
Technical life span	15 years
Dimensions (HxLxW)	78 x 53 x 117 cm
Weight	23.9 kg
Packaging weight	0.2 kg
Product certification	European Norm EN15373

GLOBAL WARMING POTENTIAL

To quantify and compare results, we use the Global Warming Potential (GWP) expressed in kg CO₂-equivalent. This is a measurement method for finding out the amount of energy required to emit 1 tonne of a gas, which is absorbed over a 100-year period. The greater the GWP, the more a particular gas warms the earth.

To comply with EN ISO 15804+A2, Casala uses the 'cradle to grave' assessment for their EPD files. The assessment covers the full life cycle of a product; from production phase to use, followed by recycling or disposal. Other EPD files often only use the 'cradle to gate' assessment, which only covers the production phase.

GWP per unit (Cradle to Grave)	54.312 kg CO ₂ eq.
GWP per unit (Cradle to Gate)	63.111 kg CO ₂ eq.
Average GWP for contract Waiting room beam seating according to the Furniture Industry Research Association (Cradle to Gate)	66.000 kg CO ₂ eq.

THE ASSUMED PERCENTAGE OF WASTE PROCESSING

Landfill	3.71 %
Incineration	19.07 %
Recycling	70.22 %
Re-use	7.00 %

DOCUMENT INFORMATION

Calculation number	ReTHiNK-130213
Declaration owner	Casala
Publisher	Casala
Program operator	Casaro
LCA software	NIBE - R<THINK LCA
Status	Valid

